

MATERIAL SAFETY DATA SHEET

Page 1 of 1

Issue No 1, Jan 2008

Name of Product: RemoTac AS™ (Spray Booth Oven Liner)

Manufacturer Drytac Europe Ltd.

Drytac Europe Ltd.
Drytac House
Filwood Road
Bristol, UK
BS16 3RY
Telephone: +44 (0) 117 958 6500
Fax: +44 (0) 117 965 4411
bristol@drytac.com

1. Product Composition

RemoTac AS™ is a white polyester film coated on both sides with acrylic adhesives (one side permanent, other side removable) and protected by a moisture stable release liner (which is removed prior to application).

2. Hazards

Chemical Stability: stable under normal conditions of use.
No critical hazards to man or environment.

3. First Aid Measures

Ingestion: immediately rinse mouth with plenty of water. Seek medical attention.
Skin Contact: not harmful. On contact with adhesive wash with soap and water.
Inhalation: in case of fire, do not breath the fumes.
Eye contact: rinse eyes with plenty of water.

4. Fire and Explosion Hazard Data

Drytac would like to emphasise that no thermal decomposition will occur if product is used correctly.
Flammability: polyester is not self-flammable but it will burn in direct contact with flame or any other high temperature ignition source. No danger of explosion.
Decomposition Products: Water vapour (H₂O), Carbon monoxide (CO) and Carbon dioxide (CO₂).
Extinguishing media: common extinguishers can be used, such as water, foam, carbon dioxide or dry extinguishers.
Fire fighting precautions: avoid breathing vapours.

5. Precautions for Safe Handling and Use

No special hazards anticipated under normal conditions of handling, storage, processing and disposal.

6. Disposal Consideration

Waste Disposal method: disposal should be in accordance with local, state or national legislation.

7. Control and Protective Measures

No protective clothing required under normal conditions of use.

8. Toxicological Information

The product is not harmful to health provided if it is handled and processed correctly.

9. Transport Information

The product is not classified as hazardous under transport regulations.

Specifications subject to change without notice.

Published information concerning Drytac Europe Ltd products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac Europe Ltd does not accept liability for risks associated with the performance of the materials in application. All Drytac Europe Ltd products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac Europe Ltd standard conditions of sale.