



## TwinTac™

### Product Description

TwinTac™ is a 50µ (2 mil) plasticised, clear PVC mounting film coated on both sides with a pressure sensitive, aqueous acrylic adhesive which is protected on both sides by a bleached Kraft blue grid release paper coated on one side with siliconised polyethylene.

### Suggested Applications

TwinTac™ is suitable for all mounting applications with the double release papers protecting the adhesive layer before is required thus preventing any contamination during handling. TwinTac™ also offers a very high level of flexibility in preparing material prior to the final mounting operation taking place. TwinTac™ is the ideal product for the production of pre-coated boards.

### Product Structure

Release Liner:	1 Side PE coated bleached Kraft Blue Grid Paper (Moisture Stable)	
Adhesive:	Aqueous Acrylic (Pressure Sensitive)	
Film:	Clear PVC	
Adhesive:	Aqueous Acrylic (Pressure Sensitive)	
Release Liner:	1 Side PE coated bleached Kraft Blue Grid Paper (Moisture Stable)	

### General Properties

Film Thickness	50µ (2mil)
Adhesive Layer	25µ (1 mil) on each side
Ratio Film/Adhesive	1/1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat resistance	70°C to 95°C (158°F to 203°F)
Peel Strength (20 min, FTM1)	23 N/25mm

### Process Settings

<b>Roller Laminator</b> Temperature: Room Temperature to 49°C (120°F) Speed: 0.3m to 1.5m (1 ft to 5 ft) per minute	<b>Press</b> NOT RECOMMENDED
---	---------------------------------

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS16 3RY, UK. Tel: +44 (0) 845-070-0660  
 Drytac Corp. (USA) – 5383 Glen Alden Drive, Richmond, Virginia 23231, USA. Telephone: 1-800-603-6610  
 Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Telephone: 1-800-353-288