

JetMounter™ Roller Laminators

The design of JetMounter™ roller laminators is the culmination of three decades of experience in the mounting and laminating business. Equipped with the performance features our customers demand, JetMounter™ roller laminators are unmatched for value.

JetMounter™ Extreme

Heated top and bottom roller laminator gives maximum flexibility.

The Jet Mounter Extreme is the most comprehensive roller laminator on the market. It offers comfortable and precise control adjustments of the material, a roll up roller for “roll to roll” processes, and has an easy global safety system with emergency stop. It is designed for use with thermal encapsulation films, as well as indoor displays, floor graphics, outdoor display, and many other applications. The JetMounter Extreme is versatile and safe for optimal productivity without major effort.

Features:

- Robust design with leveling legs for installation in uneven environments and wheels for increased mobility.
- Easy to use control panel to manage variable temperature, speed and rollers gap.
- Anti-stick silicon rollers. Two axes for take-up and two unwind roll axes. One additional un-wind for the “roll to roll” function.
- Rear rolls traction system to obtain tense, tight film and also a flat and stable result.
- Ergonomic front feeder table to ease the loading of the material.
- Easy adjustment of the film using the brakes.
- Optical safety protection. Pedal control for hands free operation. 2 global safety system with emergency stop.
- Various options possible:
 - Swing out arms.
 - Motor speed upgrade.



JM EXTREME SPECIFICATIONS

Max Laminating Width	1650mm
Max Nip Opening	40mm
Uncrated Weight	1873 lbs. (850 kg)
Width	87" (2220 mm)
Depth	31" (785 mm)
Height	52" (1320 mm)
Roller Diameter	3" (76.2 mm)
Maximum Speed	4m/minute
(Optional upgrade)	12m/minute
Maximum Roller Temperature	130° C
Power	230-240V 50Hz, 38A Single Phase

Product Code	Description
JM Extreme	1650mm - 4 Roller

Note: Delivery charges apply for all equipment. Call for rates.

DRYTAC®

Tel +44 (0)117 958 6500
 +44 (0)845 070 0660
 Email bristol@drytac.com
 Web www.drytac.com