



MHL Eclipse™

Product Description

MHL Eclipse™ is a rigid, white, thermal laminating film for displays that require 100% opacity.

Suggested Applications

Ideal for automatic recoil, re-rollable pop-up graphic display systems or the latest range of light weight graphic display panels.

Features and Benefits

Offering 100% opacity, MHL Eclipse™ gives wide format printers the option to produce two-sided images without any light transference. MHL Eclipse™ is water, oil, acid, and alkali resistant. It can also be die cut.

General Properties

Thickness	5 mil, 10 mil, 15 mil
Finish	White
Base Film	Polyester/ metal foil/ polyester
Adhesive	Co-extruded copolymer
Initial Tack	None
Release Liner	None
Outdoor Durability	3 Months

Peel Strength (lbf/in)

5 mil	10 mil	15 mil
15	25	25

Process Settings

Roller Laminator	Press
185° F - 195° F (85° C - 90° C)	Not Recommended

Specifications subject to change without notice.

Published information concerning Drytac products is based upon research which the company believes to be reliable and accurate. Such information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Drytac does not accept liability for risks associated with the performance of the materials in application. All Drytac products are subjected to carefully quality control throughout the manufacturing process and are sold subject to Drytac standard conditions of sale.

Drytac Europe Ltd (UK) – Drytac House, Filwood Road, Fishponds, Bristol, BS163RY, Uk. Tel. +44(0) 845-070-0660

Drytac Corp. (USA) – 5601 Eastport Boulevard, Richmond, Virginia 23231, USA. Tel. 1-800-603-6610

Drytac Canada Inc. (Canada) – 220 Caldari Road, Concord, Ontario, L4K 3X5, Canada. Tel. 1800-353-2883