



## HOT GLASS VACUUM PRESS

Based on our unique, patented heating technology, the Hot Glass Vacuum Press sets the standard for excellence in mounting, heatsealing and canvas bonding, and is well regarded by picture framers and other finishing professionals for its ability to produce consistent, high-quality results.

The Hot Glass Vacuum Press can handle a wide range of presentation materials from foam board and wood to photos, art prints and delicate fabrics.



### State of the art heating system

The top panel of the press is comprised of two sheets of reinforced tempered glass. The inner surface of the lower sheet has an invisible conductive film embedded in it. A controlled electric current is passed through this conductive film, creating a highly efficient heating system. A sensor on the glass monitors and controls the temperature by means of a digital thermostat.

### Adjustable temperature control

So that all kinds of artworks can be mounted - even those that may be subject to damage by heat.

### Glass top

The transparent top panel offers a high level of operator confidence as work can be viewed throughout most bonding processes. The glass is extremely smooth and scratch resistant.



### Adjustable timer control

When processing large volumes of work, the programmable timer can be set to the minimum time required for each batch of work, increasing productivity.

### Automatic Electronic Timer

With manual override switch.

# DRYTAC<sup>®</sup>

## HOT PRESS



### Adjustable pressure control

Minimises even heavy creases and wrinkles - while ensuring that delicate items such as foamboard and embossed prints are not crushed.

### Dedicated vacuum pump

The factory matched vacuum pump ensures that pressure is never pulled too quickly or slowly.

### HOT GLASS VACUUM PRESS

Model	HGP260	HGP360	HGP560
Weight	72 kgs	111 kgs	210 kgs
Width	975mm	1194mm	1422mm
Depth	1300mm	1800mm	2615mm
Height	160mm	160mm	950mm inc. stand
Time to Vacuum (secs)	20	30	30
Time to Temperature (mins)	12	12	15
Working Dimension	890 x 1195mm	1095 x 1705mm	1276 x 2496mm
<b>Packed Weights &amp; dimensions</b>			
Weight	90 kgs	145 kgs	447 kgs
Width	1400mm	1920mm	2800mm
Depth	1150mm	1360mm	1620mm
Height	320mm	320mm	620mm
Voltage	230 V 50/60Hz	230 V 50/60Hz	230 V 50/60Hz
Wattage	2500 W	4200 W	5750 W
Current (Amps)	11	18	25